

QL-580N

DK Labels



Versatile and Easy to use thermal label



Copy

Catalogue Spec

- Easy to operate – print directly from MS Word, Excel or Outlook
- Network-Ready, perfect for sharing
- Professional – built in automatic label cutter leaves a clean cut edge.
- Quick and effective - prints up to 68 labels per minute
- High Quality 300 x 600dpi resolution printing
- No Paper Jams, No Ink or Toner needed, No label wastage
- Easy peel labels
- Print continuous length or pre sized die cut labels
- Includes 62mm black on white continuous length tape (8m) and standard address labels (100 labels)
- Prints 12mm – 62mm wide labels

What's in the Box

- 62mm black on white continuous length tape
- Standard address label (100 labels)
- CD ROM
- Setup and operation guide
- USB Cable
- AC adapter
- DK roll guide
- Cleaning sheet

Hardware

QL-580N	
Dimensions	133mm(W) x 240mm(D) x 143mm(H)
	5.2"(W) x 9.4"(D) x 5.6"(H)
Weight	1.2kg (without DK roll)
	2.65pounds (without DK roll)
Housing Color	Black
Key Board	No
Number of Keys	3 (On/Off, Feed, Cut)
Cutter	Durable Auto cutter (User unreplaceable)
Auto Half Cutter	No
Power supply	Internal S/W Power Supply
LCD	No
LED	1 (3 color - Green, Red, Orange)
Print Method	Direct Thermal
Attachments	CD-ROM (P-touch Editor 5.0 for Windows, P-touch Address Book 1.1, P-touch Editor 5.0 for Mac, Printer Driver, User's Guide, NETWORK USER'S GUIDE, P-touch Template tools, ESC/P tools)
	Setup & Operation Guide
	DK Rolls Line-up Guide
	Cleaning Sheet
	USB cable
	Warranty card
	DK-11201 (29mm x 90mm Standard Address Labels) Starter roll (100 labels)
	DK-22205 (62mm Continuous Length Paper Tape) Starter roll (8 m)
	AC Power cord
	EEE insertion
Roll Type	DK rolls (DK Die-cut Labels / DK Continuous Length Tape)
Roll Width	Max. Label width 62mm (2.4")
Print Head	300 dpi / 720 dots
Print Speed	Max. 110 mm (4.3") / sec.
	Max. 68 standard labels / min.
Strap / Handle	No
Computer Interface	USB, RS-232C, 10/100 BASE-TX Wired Ethernet
LCD Mylar	No
Mylar Sticker	No